



End View

Top View


Notes:

Notes:
ASTM C 1613 Compliant
4" Inlet/Outlet (Standard)
12" Holes in Baffle Wall
2/3 - 1/3 Compartment Capacity

ASTM C 990 Butyl Sealant



Side View



Baffle View

Specifications

Concrete: 5,000 psi minimum strength (28 day)

Reinforcing: Primary reinforcement will be rebar.

Risers: Grade rings and manhole frames and covers sold separately.

Sealant: Sealant used in the seam of the tank will meet or exceed ASTM C990.

Pipe Penetrations: Inlet and outlets are fitted with seals that meet or exceed all ASTM C923 specifications.

Partition Wall: The partition wall, if present, is poured monolithic with the foundation. **Drawing:** All measurements are accurate within ± 1 inch.

Tank Warranty: See Terms and Conditions

Centroid(s): Lid (91, 39), Base (91, 39)

BARGER PRECAST

Weights

Weights
Top - 11,027 lb
Bottom - 14,518 lb

Anti-Float Protection

Installation: The tank hole is not to be more than 18 in. longer and wider than the tank. There shall be a minimum of 6" of 3/4" stone bedding. Do not install across path of vehicles or heavy equipment. This tank is designed for one hundred fifty pounds per square foot (150 lb/ft²) uniform loading on the top of the tank with a max backfill cover of 36" and a minimum of 6".

2,500 Gallon Grease Trap Hallsdale-Powell

P.O. Box 370 - Kingston TN 37763
Phone 888.882.5860 - BargerPrecast.com