



Top View

## Stencil

**Notes:**  
 ASTM C 1613 Compliant  
 HS20 Traffic Rated  
 4" Inlet/Outlet (Standard)  
 4" PVC 90 in Baffle Wall  
 2/3 - 1/3 Compartment Capacity

[Date of manufacture]  
 4000 Gallons HS20  
 150 lb/sq ft  
 Max Cover: 3 ft  
 [Inlet/Outlet Size]  
 "Inlet" and "Outlet"

ASTM C 990 Butyl Sealant



Side View

## Specifications

**Concrete:** 5,000 psi minimum strength (28 day)

**Reinforcing:** Primary reinforcement will be rebar.

**Risers:** Grade rings and manhole frames and covers sold separately.

**Sealant:** Sealant used in the seam of the tank will meet or exceed ASTM C990.

**Pipe Penetrations:** Inlet and outlets are fitted with seals that meet or exceed all ASTM C923 specifications.

**Partition Wall:** The partition wall, if present, is poured monolithically.

**Drawing:** All measurements are accurate within  $\pm 1$  inch.

**Tank Warranty:** See Terms and Conditions.

**Centroid(s):** Lid (125, 49), Riser (127, 49) Base (126, 49)

# BARGER PRECAST

P.O. Box 370 - Kingston TN 37763  
 Phone 888.882.5860 - BargerPrecast.com

### Weights

Top - 25,168 lb  
 Riser - 19,108 lb  
 Base - 38,625 lb

### Anti-Floot Protection

0" of water

**Installation:** The tank hole is not to be more than 18 in. longer and wider than the tank. There shall be a minimum of 6" of 3/4" stone bedding. This tank is designed for HS20 traffic loads with a max backfill cover of 6' and a minimum of 6".

## 6,000 Gallon HS20 Grease Trap

Date: 2.162017

Drawn By: Eric Barger

Updated: 7.222024