


Top View



Specifications

Concrete: 5,000 psi minimum strength (28 day)
Reinforcing: Primary reinforcement will be rebar.

Risers: Grade rings and manhole frames and covers sold separately.

Sealant: Sealant used in the seam of the tank will meet or exceed ASTM C990.

Pipe Penetrations: Inlet and outlets are fitted with seals that meet or exceed all ASTM C923 specifications.

Partition Wall: The partition wall, if present, is poured monolithically. Drawing: All measurements are accurate within $\pm\ 1$ inch.

Tank Warranty: See Terms and Conditions.

Centroid(s): Lid (123, 54), Riser (126, 54), Base (125, 54)

RECAST

Weights

Top - 13,377 lb Riser - 16,872 lb Bottom - 30,174 lb

Anti-Float Protection

27" of water

Installation: The tank hole is not to be more than 18 in. longer and wider than the tank. There shall be a minimum of 6" of 3/4" stone bedding. Do not install across path of vehicles or heavy equipment. This tank is designed for one hundred fifty pounds per square foot (150 lb/ft2) uniform loading on the top of the tank with a max backfill cover of 36" and a minimum of 6".

P.O. Box 370 - Kingston TN 37763 Phone 888.882.5860 - BargerPrecast.com

8,000 Gallon Septic Tank

Drawn By: Eric Barger Updated: 7.232025 11.212021